

OTDR Report (1310 nm (9 μm))

General Information

File name:	13_1310.trc	Customer:	ADNOC
Test date:	14-Feb-24	Company:	PAN ARABIA
Test time:	4:26 PM	Fiber ID:	13
Cable ID:	FAR5 to SS6A (C) B (B-A)		
Job ID:	0500831		
Comments:	END TO END TEST		


Locations

	Location A	Location B
Location	SS6A	FAR5
Operator	PANDA	HABEEB
Model	MAX-720C-Q1-EA-EI	
Serial number	1206159	
Calibration date	29-Mar-23 (UTC)	

Results

Span length:	1.1480 km	Average loss:	0.677 dB/km	Injection level:	25.4 dB
Span loss:	0.777 dB	Average splice loss:	---		
Span ORL:	39.47 dB	Maximum splice loss:	---		

Graph



Markers

Marker	Position (km)	Value (dB)	A-B LSA attenuation:	0.942 dB/km	A-B average loss:	-7.299 dB/km
a	0.0000	25.425	A-B LSA loss:	1.084 dB	4-point Event Loss:	-8.798 dB
A	0.0000	25.425	A-B ORL:	37.80 dB	Maximum reflectance:	-43.7 dB
B	1.1502	33.820				
b	1.1502	33.820				

OTDR Report (1310 nm (9 μm))

Event Table

Type	No.	Pos./Length (km)	Loss (dB)	Reflectance (dB)	Attenuation (dB/km)	Cumulative (dB)
First Connector	1	0.0000	---	-43.7		0.000
Section		1.0570	0.361		0.341	0.361
Reflective	2	1.0570	0.399	-59.0		0.759
Section		0.0910	0.018		0.196	0.777
Reflective	3	1.1480	---	> -23.8		0.777

Macrobend

Position (km)	Delta Loss (dB)

Pass/Fail Thresholds

	1310 nm (9 μm)

Test Parameters

	A → B
Wavelength (nm)	1310 nm (9 μm)
Range (km)	1.3000
Pulse (ns)	100
Duration (s)	5

Test Settings

	A → B	Macrobend Wavelengths	Macrobend Delta Loss (dB)
IOR	1.467700		
Backscatter (dB)	-79.45		
Helix factor (%)	0.00		
Splice loss detection threshold (dB)	0.020		
Reflectance detection threshold (dB)	-72.0		
End-of-fiber detection threshold (dB)	5.000		

OTDR Report (1550 nm (9 μm))

General Information

File name:	13_1550.trc	Customer:	ADNOC
Test date:	14-Feb-24	Company:	PAN ARABIA
Test time:	4:27 PM	Fiber ID:	13
Cable ID:	FAR5 to SS6A (C) B (B-A)		
Job ID:	0500831		
Comments:	END TO END TEST		


Locations

	Location A	Location B
Location	SS6A	FAR5
Operator	PANDA	HABEEB
Model	MAX-720C-Q1-EA-EI	
Serial number	1206159	
Calibration date	29-Mar-23 (UTC)	

Results

Span length:	1.1478 km	Average loss:	0.469 dB/km	Injection level:	24.2 dB
Span loss:	0.538 dB	Average splice loss:	---		
Span ORL:	41.70 dB	Maximum splice loss:	---		

Graph



Markers

Marker	Position (km)	Value (dB)	A-B LSA attenuation:	0.849 dB/km	A-B average loss:	-8.210 dB/km
a	0.0000	24.705	A-B LSA loss:	0.976 dB	4-point Event Loss:	-9.673 dB
A	0.0000	24.705	A-B ORL:	39.24 dB	Maximum reflectance:	-42.9 dB
B	1.1502	34.148				
b	1.1502	34.148				

OTDR Report (1550 nm (9 μm))

Event Table

Type	No.	Pos./Length (km)	Loss (dB)	Reflectance (dB)	Attenuation (dB/km)	Cumulative (dB)
First Connector	1	0.0000	---	-43.7		0.000
Section		1.0566	0.201		0.190	0.201
Reflective	2	1.0566	0.304	-59.7		0.505
Section		0.0912	0.034		0.371	0.538
Reflective	3	1.1478	---	> -24.2		0.538

Macrobend

Position (km)	Delta Loss (dB)

Pass/Fail Thresholds

	1550 nm (9 μm)

Test Parameters

	A → B
Wavelength (nm)	1550 nm (9 μm)
Range (km)	1.3000
Pulse (ns)	100
Duration (s)	5

Test Settings

	A → B	Macrobend Wavelengths	Macrobend Delta Loss (dB)
IOR	1.468325		
Backscatter (dB)	-81.87		
Helix factor (%)	0.00		
Splice loss detection threshold (dB)	0.020		
Reflectance detection threshold (dB)	-72.0		
End-of-fiber detection threshold (dB)	5.000		