

OTDR Report (1310 nm (9 μm))

General Information

File name:	91_1310.trc	Customer:	ADNOC
Test date:	14-Feb-24	Company:	PAN ARABIA
Test time:	3:01 PM	Fiber ID:	91
Cable ID:	FAR3 to FAR0 1A (B-A)		
Job ID:	0500831		
Comments:	END TO END TEST		


Locations

	Location A	Location B
Location	FAR3	FAR0
Operator	PANDA	HABEEB
Model	MAX-720C-Q1-EA-EI	
Serial number	1206159	
Calibration date	29-Mar-23 (UTC)	

Results

Span length:	2.4447 km	Average loss:	0.487 dB/km	Injection level:	25.2 dB
Span loss:	1.189 dB	Average splice loss:	---		
Span ORL:	36.84 dB	Maximum splice loss:	---		

Graph



Markers

Marker	Position (km)	Value (dB)	A-B LSA attenuation: A-B LSA loss: A-B ORL:	0.615 dB/km 1.507 dB <30.77 dB	A-B average loss: 4-point Event Loss: Maximum reflectance:	-6.800 dB/km -17.520 dB > -25.7 dB
a	0.0000	25.457				
A	0.0000	25.457				
B	2.4505	42.119				
b	2.4505	42.119				

OTDR Report (1310 nm (9 μm))

Event Table

Type	No.	Pos./Length (km)	Loss (dB)	Reflectance (dB)	Attenuation (dB/km)	Cumulative (dB)
First Connector	1	0.0000	---	-44.1		0.000
Section		1.0564	0.361		0.341	0.361
Reflective	2	1.0564	0.342	-55.6		0.702
Section		1.3883	0.487		0.351	1.189
Reflective	3	2.4447	---	> -22.9		1.189
Section		1.3947	---		---	---
Reflective		3.8395	---	-54.2		---
Section		1.0526	---		---	---
Merged Events		4.8920	---	-32.3		---

Macrobend

Position (km)	Delta Loss (dB)

Pass/Fail Thresholds

	1310 nm (9 μm)

Test Parameters

	A → B
Wavelength (nm)	1310 nm (9 μm)
Range (km)	5.0000
Pulse (ns)	100
Duration (s)	5

Test Settings

	A → B	Macrobend Wavelengths	Macrobend Delta Loss (dB)
IOR	1.467700		
Backscatter (dB)	-79.45		
Helix factor (%)	0.00		
Splice loss detection threshold (dB)	0.020		
Reflectance detection threshold (dB)	-72.0		
End-of-fiber detection threshold (dB)	5.000		

OTDR Report (1550 nm (9 μm))

General Information

File name:	91_1550.trc	Customer:	ADNOC
Test date:	14-Feb-24	Company:	PAN ARABIA
Test time:	3:01 PM	Fiber ID:	91
Cable ID:	FAR3 to FAR0 1A (B-A)		
Job ID:	0500831		
Comments:	END TO END TEST		


Locations

	Location A	Location B
Location	FAR3	FAR0
Operator	PANDA	HABEEB
Model	MAX-720C-Q1-EA-EI	
Serial number	1206159	
Calibration date	29-Mar-23 (UTC)	

Results

Span length:	2.4443 km	Average loss:	0.304 dB/km	Injection level:	24.1 dB
Span loss:	0.742 dB	Average splice loss:	---		
Span ORL:	38.80 dB	Maximum splice loss:	---		

Graph



Markers

Marker	Position (km)	Value (dB)	A-B LSA attenuation:	0.426 dB/km	A-B average loss:	-7.172 dB/km
a	0.0000	24.673	A-B LSA loss:	1.043 dB	4-point Event Loss:	-18.064 dB
A	0.0000	24.673	A-B ORL:	<30.61 dB	Maximum reflectance:	> -25.5 dB
B	2.4505	42.247				
b	2.4505	42.247				

OTDR Report (1550 nm (9 μm))

Event Table

Type	No.	Pos./Length (km)	Loss (dB)	Reflectance (dB)	Attenuation (dB/km)	Cumulative (dB)
First Connector	1	0.0000	---	-44.5		0.000
Section		1.0566	0.200		0.189	0.200
Reflective	2	1.0566	0.236	-56.2		0.436
Section		1.3877	0.307		0.221	0.742
Reflective	3	2.4443	---	> -23.6		0.742
Section		1.3948	---		---	---
Reflective		3.8391	---	-55.6		---
Section		1.0528	---		---	---
Merged Events		4.8919	---	-27.3		---

Macrobend

Position (km)	Delta Loss (dB)

Pass/Fail Thresholds

	1550 nm (9 μm)

Test Parameters

	A → B
Wavelength (nm)	1550 nm (9 μm)
Range (km)	5.0000
Pulse (ns)	100
Duration (s)	5

Test Settings

	A → B	Macrobend Wavelengths	Macrobend Delta Loss (dB)
IOR	1.468325		
Backscatter (dB)	-81.87		
Helix factor (%)	0.00		
Splice loss detection threshold (dB)	0.020		
Reflectance detection threshold (dB)	-72.0		
End-of-fiber detection threshold (dB)	5.000		